



## Specifications Ledvance LED Downlight Surface IP65 Aluminium Black 45W 4950lm 36D - 840 Cool White | IP65

[View Product](#)

### General Information

|                      |                                         |
|----------------------|-----------------------------------------|
| SKU                  | 247092                                  |
| EAN                  | 4058075769274                           |
| Manufacturer Code    | 4058075769274                           |
| Brand                | Ledvance                                |
| Manufacturer Name    | DL SURFACE DN 250 P 45W 840 36D IP65 BK |
| Budgetlight warranty | 5 Years                                 |
| Average Lifetime (h) | 100000                                  |

### Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Tiltable                    | No              |
| Technology                  | LED Integrated  |
| Wattage                     | 45W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Including bulb              | Yes             |

|                       |                    |
|-----------------------|--------------------|
| Beam Angle (degree)   | 36                 |
| Luminous Flux (Lumen) | 4950lm             |
| Lumen per watt        | 110                |
| Power factor          | >0.90              |
| Unified Glare Rating  | < 19 - For offices |
| Optical Cover         | PC (Polycarbonate) |
| Product Type Category | LED Downlight      |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Surface                     |
| Cut out (mm)           | 250                         |
| IP-rating              | IP65                        |
| Impact Protection (IK) | IK06 - 1 joule              |
| Operating Temperature  | -20 to +40                  |
| Housing                | Aluminium                   |
| Colour of the Fixture  | Black                       |
| Colour of material     | Black                       |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |
| Product Serie          | DOWNLIGHT SURFACE IP65      |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 125 |
| Diameter (mm) | 250 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**